

WT-500 - Durable floor marking tape

Characteristic are the bevelled edges, which prevent rapid damage in general traffic with pallet trucks, forklifts or cleaning machines. Replaces the marking with color and can therefore be used immediately.

Applications: Indoor

Technical specifications

| | |
|-------------------------|-----------------|
| Material: | PVC |
| Thickness: | 1,10 mm |
| Glue: | Acrylic |
| Adhesive power: | ≥ 16 N / 2,5 cm |
| Tensile force: | |
| Dynamic shear: | |
| Temperature resistance: | -20°C to +55°C |
| Processing temperature: | +15°C to +25°C |
| Storage: | |



Available colours

- Transparent
- Yellow
- Red
- Light blue
- Blue
- Light green
- Green
- Purple
- Orange
- Brown
- Pink
- White
- Light grey
- grey
- Dark grey
- Black
- Black/White
- Yellow/Black
- Red/White
- Blue/White
- Green/White
- Photoluminescence
- Photoluminescence/Black

Applications

- Concrete / smooth
- EP-/ Pu / MMA coating
- EP-/ Pu / MMA coating antislip
- Tiles
- Concrete paving
- Asphalt

Application information

When laying the tape, the surface must be clean, free from grease, dust and dry. We recommend that you label the laying line with chalk first.

Note / Information

It is possible to drive over the belt with floor conveyors. Turning and turning on the conveyor with floor conveyors or similar heavy vehicles should be avoided.

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:
21.09.2020

Obchodné zastúpenie a aplikácie pre Slovensko

Tel.: +421 915 896 527
eMail: info@danmat.sk
www.vodorovneznačenie.sk

DanMat s.r.o.
Švermová 39
036 01 Vrútky, Slovensko