

WT-5645 - Anti-slip tape conformable, Slip class R11

The climate-stable tape with poly-coated protective paper offers absolute dimensional stability and good Stan properties, lasting and uniform transparency, high shear strength and a good temperature resistance.

Applications: Indoor & Outdoor

Technical specifications

Material: Soft aluminum

Thickness: 0,6 mm

Glue:

Adhesive power: ca. 15N / 25 cm (nach 24 h)

Tensile force:

Dynamic shear:

Temperature resistance: - 20°C to +80°C

Processing temperature: +15°C to +25°C

Storage:



Available colours

- Transparent
- Yellow
- Red
- Light blue
- Blue
- Light green
- Green
- Purple
- Orange
- Brown
- Pink
- White
- Light grey
- grey
- Dark grey
- Black
- Black/White
- Yellow/Black
- Red/White
- Blue/White
- Green/White
- Photoluminescence
- Photoluminescence/Black

Applications

- Concrete / smooth
- EP-/ Pu / MMA coating
- EP-/ Pu / MMA coating antislip
- Tiles
- Concrete paving
- Asphalt

Application information

The substrate must be clean, free from grease, dust and dry. For outdoor applications, it is essential to apply primer no. 5 as a primer! Strictly follow the installation instructions!

Note / Information

It is possible to drive over the belt with material handling equipment. Turning and turning on the conveyor with floor conveyors or similar heavy vehicles should be avoided.

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:
21.09.2020

Obchodné zastúpenie a aplikácie pre Slovensko

Tel.: +421 915 896 527
eMail: info@danmat.sk
www.vodorovneznamenie.sk

DanMat s.r.o.
Švermová 39
036 01 Vrútky, Slovensko