

WT-6000 - steel aisle marking

Durable, durable, self-adhesive steel floor marking tape. Ideal for dry areas, quick to stick on, wear-resistant, easy to clean, drivable immediately, replaces the marking with paint.

Applications: Indoor

Technical specifications

Material:	Steel
Thickness:	0,7 mm
Glue:	Acrylic
Adhesive power:	13 N / 10 mm
Tensile force:	
Dynamic shear:	
Temperature resistance:	-20°C to +90°C
Processing temperature:	+15°C to +25°C
Storage:	



Available colours

- Transparent
- Yellow
- Red
- Light blue
- Blue
- Light green
- Green
- Purple
- Orange
- Brown
- Pink
- White
- Light grey
- grey
- Dark grey
- Black
- Black/White
- Yellow/Black
- Red/White
- Blue/White
- Green/White
- Photoluminescence
- Photoluminescence/Black

Applications

- Concrete / smooth
- EP-/ Pu / MMA coating
- EP-/ Pu / MMA coating antislip
- Tiles
- Concrete paving
- Asphalt

Application information

The substrate must be smooth, dry, free of grease and dust. The application is simplified if you mark the laying line with chalk. The tape can be cleaned with warm water and soap. The tape can be easily removed by pulling off the floor, almost residue-free.

Note / Information

It is possible to drive over the belt with material handling equipment. Turning and turning on the conveyor with floor conveyors or similar heavy vehicles should be avoided.

The product information listed above is compiled to the best of our knowledge and based on current data. These characteristics are typical, but they do not constitute a specification. The information provided to the customer does not relieve the customer of his obligation to test for suitability for the intended applications and procedures.

Date:
04.11.2020

Obchodné zastúpenie a aplikácie pre Slovensko

Tel.: +421 915 896 527
eMail: info@danmat.sk
www.vodorovneznacenie.sk

DanMat s.r.o.
Švermová 39
036 01 Vrútky, Slovensko